



Marking to ATEX 94/9/EC Directive: $\text{Ex II 2 G Ex d IIC Gb / II 2 G Ex e IIC Gb / II 2 D Ex tb IIIC Db}$

Zone: 1, 2, 21, 22 , Gas Group IIC

Compliance with: IEC 60079-0:2011, IEC 60079-1:2007, IEC 60079-7:2007, IEC 60079-31:2008

EC Type Examination Certificate: ISSeP 12 ATEX 027



FEATURES

- Dual certified Ex 'd' IIC flame proof and Ex 'e' II increased safety, helps to reduce specification errors.
- In accordance with BS 6121 : PAR 1 : 1989 type A2 for non-armoured, elastomer and plastic insulated cables.
- For outdoor or indoor use with seal protection degree IP66.
- Provides a seal on outer sheath of cable.
- High pull out resistant seal on the cable sheath.
- Wide cable acceptance range for easy selection.
- Operating temperature range: -50 °C to +100 °C.
- Materials and Finish: Manufactured as standard in brass with optional Nickel or Galvanized plating.
Also available in stainless steel.



OPTIONAL ACCESSORIES

- Nickel or Galvanized plating for brass cable gland.
- Sealing washer.
- Earth tag.
- Locknut.
- Shroud.

نور محور فارس
تولید کننده تجهیزات الکتریکی ضد انفجار

NM SWITCHGEAR

Explosion Proof Electrical Supplies

